# Code signing flaw in macOS

#### > whoami

Thomas Reed Director of Mac & Mobile @ Malwarebytes

**Othomasareed** 



#### Not rocket science

..but why should it be when we have threats like this?

# Code signing on Mac

- > Most apps code signed today
- > Unsigned apps not allowed by default
- > macOS verifies code signature before running downloaded apps





# Code signing on Mac




- Apps are "quarantined" when downloaded
- > Gatekeeper only checks code signature for quarantined apps
- After opening, quarantine flag is removed
- Code signature is never checked again!




# Infecting an app

- > Rename "good" to something else like "0"
- Add malicious executable named "good"
- "good" executable loads "0" to make the app seem normal



# Infecting an app





You have dysentery.

#### How hard is this?






- Not very!
- > 22 lines of Swift code malicious executable
- > 18 lines of AppleScript dropper part 1
- > 16 lines of shell script dropper part 2



#### Exceptions



- Apple's apps can't be modified
- > If you try it, they crash
- > Malicious code still runs!



#### Exceptions

- Some third-party apps have self-protection
- > If you change them, they'll let the user know
- Malicious code still runs!





Something has modified Pacifist's application bundle. The application could be damaged, or could be infected by a virus. Please download an unaltered copy of Pacifist.

OK

#### Potential giveaways,

- Doubled Dock icons.
- > Malicious process shows as bouncing icon
- Original process appears normally
- > Can be prevented























#### Potential giveaways,

- > Two processes in Activity Monitor
- > Two processes in ps output
- Could make this less suspicious fairly easily

```
Hyperion:~ thomas$ ps -axo command | grep good.app
/Applications/good.app/Contents/MacOS/good
/Applications/good.app/Contents/MacOS/0
grep good.app
Hyperion:~ thomas$
```

#### How to detect

> Use osquery to check signature



```
Hyperion:~ thomas$ osqueryi --line 'select * from signature where path="/Applical-tions/good.app"'

path = /Applications/good.app

signed = 1

identifier = com.thesafemac.good

cdhash = 7bdebb6406c5148f5b055971af11864da4633d40

team_identifier = DKYMKWTFCU

authority = Developer ID Application: Thomas Reed (DKYMKWTFCU)

Hyperion:~ thomas$
```

#### How to detect

> Use osquery to check signature



```
Hyperion:~ thomas$ osqueryi --line 'select * from signature where path="/Applications/good.app"'

path = /Applications/good.app

signed = 0

identifier = MalTest-55554944f1486d7a59f535fabef31b690dbbc92b

cdhash = 93c51b7dc46ca82eba78e00b93685ccb914757b6


team_identifier =

authority =

Hyperion:~ thomas$
```

#### Naughty or nice?

- > Possible solution: Santa https://github.com/google/santa
- Use in lockdown mode to allow only whitelisted apps to run
- > Modified apps will be blocked



# Naughty or nice?

#### Santa

The following application has been blocked from executing because its trustworthiness cannot be determined.

Application good

Filename good

Path /Applications/good.app/Contents/MacOS/good

Publisher Not code-signed

| 41bf94e3896dacc15fc00f09b2a3eafe | fcc28bfe43c3e58f73480a8b5ddf2f65

Parent launchd (1)

User test

Prevent future notifications for this application for a day

Ignore



# Naughty or nice?

- > Pros:
  - > Difficult to bypass
- > Cons:
  - > Whitelisting will keep you jumping with user requests!
  - Unrealistic for certain users (eg, developers)



#### Solutions?

- > Apple could check signatures more often
  - > Potentially resource-heavy
- > Developers need to check their own signatures

# Bonus points

| 淾          | Space Invaders10      | points |
|------------|-----------------------|--------|
| <u></u> .  | Blinky (PAC-MAN)15    | points |
| **         | 📫 📫 🧲                 | points |
| <b>9</b> 8 | 戻                     | points |
| ٠.         |                       | points |
| 380        | Spider (Centipede)100 | points |
| Ç,         |                       | points |
|            |                       | points |